

CLEAR-SHIELD™

H I G H P E R F O R M A N C E R O L L I N G D O O R

The Corrosion-Proof, Full-Vision, Rolling Door for Car Washes.

The Clear-Shield offers full visibility, wind protection and reliability—without corrosion. It protects customers and vehicles outside the wash bay from sprays due to windy conditions. The clear UV-resistant vinyl panels provide natural light and the ability to see inside the bay. The door also helps inhibit freezing by dampening winds that pass through heated bays.

The Clear-Shield is safe, low maintenance, and it can take a hit. The soft, self-repairing, Break-Away™ bottom bar won't hurt customers or damage cars if accidentally hit. After popping out, the bar automatically reinserts itself into the guides and resumes normal operation.



Shown with custom/painted hood.

Wind Control - Panel helps control winds and sprays for improved car wash operation and protection.

Non-Corrosive - Corrosion-proof barrel, roll covers and side guides virtually eliminate the potential for rust.

Full Visibility - Full visibility through optional three full-width vision panels.

Self-Repairing - The soft, padded Break-Away™ bottom bar automatically “self-repairs” after popping out by reinserting itself into the guides.

Safe - Dual electric photo eyes and padded bottom bar ensure minimal contact and won't hurt customers or cars if accidentally hit.

Speed Options - The Clear-Shield door opens and closes at 16 inches per second with an optional 32 inches per second model for a tunnel wash providing a faster flow of customers through the bay.

Versatility - The Clear-Shield is ideal for automatic, self-service wash bays, and other high moisture, frequent use applications requiring visibility and wind control.

RYTEC
CORPORATION
Driving The Door Industry.™

CLEAR-SHIELD™

H I G H P E R F O R M A N C E R O L L I N G D O O R

Specifications: Subject to change

Model: Rytec® Clear-Shield™

Standard Size: Manufactured to exact opening dimensions up to 12 feet wide by 12 feet high. Consult factory for special sizes.

Door Panel: UV-protected, reinforced wear-resistant PVC fabric. Consult factory for color options.

Side Frames: Reinforced composite, non-corrosive, pultruded fiberglass side frames.

Bottom Bar: Soft, padded Break-Away™ bottom bar with self-repairing capability.


Drive System: ¾ hp three-phase single speed unit with direct drive through integral gear box.

Travel Speed: Opens at 16 inches per second (standard) with an optional 32 inch per second model for tunnel wash.

Electrical Controls: Thru-beam photo eyes are standard.

Control Unit: Integrated, door control logic.

Warranty: One-year limited warranty on materials and workmanship.



▲ **Padded Break-Away™, Self-Repairing Bottom Bar**
The padded bottom bar automatically "self-repairs" by reinserting itself into the guides at the top of the door.



▲ **Visibility Options**
Two or three full-width vision panels are available.



▲ **Low Profile**
The low profile allows the door to fit virtually anywhere.



One Cedar Parkway
Jackson, WI 53037-0403
Phone: 262-677-9046
Fax: 262-677-2058
Toll Free: 888-GO-RYTEC
Email: info@rytecdoors.com
Web: www.rytecdoors.com